

-MDX 500-

What's new in this version / Change Log

Version 5.211

- 1.- The transmodulator tool has been updated.

Version 5.209

- 1.- The problem when tuning an analog signal has been solved.
- 2.- The transmodulator tool has been updated.

Version 5.207

- 1.- Fixed a problem with the standby mode.
- 2.- Transmodulator tool: new CAM settings added.
- 3.- Transmodulator tool: HxAR 100 version now is displayed in decimal.
- 4.- Transmodulator tool: The OSD has been improved.
- 5.- Transmodulator tool: Log messages are longer.
- 6.- Transmodulator tool: When changing the SID, SID is displayed in the list instead of the LCN.
- 7.- Transmodulator tool: Added transmodulators settings.

Version 5.200

- 1.- The transmodulator tool has been improved.
- 2.- Transmodulator tool: Support for transmodulators with CI added.

Version 5.123

- 1.- The detection of the SATCR carriers has been improved.
- 2.- Transmodulator tool: The option "Auto symbol rate" in the model HS2CT 100 has been deleted.
- 3.- Transmodulator tool: The saturation problem when adding services to the models HSTT 100, HS2CT 100 and HS2TT 100 has been solved.
- 4.- Transmodulator tool: The name of the "FEC mode" by "DVB" option in the input configuration menu of the models HS2TT 100 and HS2CT 100 has been modified.
- 5.- The total time of commands SATCR and DiSEqC has been reduced in order to avoid problems with some switch models.
- 6.- The list of the satellite finder (Sat finder) has been updated.

Version 5.116

- 1.- Transmodulator tool: Support for HSTT 100, HS2TT 100 and HS2CT added.
- 2.- It improves the detection of the IF carrier of SATCR
- 3.- Datalogger: If the field strength meter was in SATCR mode, when measuring a satellite program that was not SATCR, the measure was wrong.
- 4.- Updating of text in the transmodulator tool.

Version 5.108

- 1.- The transmodulator programming tooling is added.

Version 5.100

- 1.- The C/N value is shown in the measures window in satellite
- 2.- Mistake in program mode when deleting or re-naming the current program and pressing 123/ABC keys, solved

Version 5.97

- 1.- Measure of MER in satellite improved
- 2.- Visualization of C/N measure in satellite band removed
- 3.- Automatic attenuator in digital mode improved
- 4.- Added: Noise Margin (instead "quality")
- 5.- Error 508 when the field strength meter runs in program mode corrected
- 6.- New languages added: Swedish

- 7.- It corrects a mistake about name redrawing when starting the field strength meter in program/group mode.
- 8.- It corrects a problem when trying to tune in a DVB-H signal as 11615H DVB S2 in Hispasat.
- 9.- Datalogger: It corrects a mistake in the name of the measure points (as "TEXT_090525_0").
- 10.- Datalogger: It corrects a mistake in the filter selection (auto and manual).
- 11.- Satfinder: Satellites added. *In order to load the new files, make values by default or use the "load satellites" menu option.*

Version 5.80

- 1.- Fixed error when exporting program with name like "E38.2".
- 2.- Fixed GMT error after factory default.
- 3.- Fixed spectrum drawing in satellite.
- 4.- Improved SATCR.
- 5.- Added temperature correction in datalogger spectrum.
- 6.- Some scripts of text resources have been updated.
- 7.- Problem in the identification of satellites in SATFINDER tool corrected.
- 8.- It corrects a mistake in datalogger when making repetitive measures with names with underscore.
- 9.- It corrects a mistake in the information bar about feeding.
- 10.- It corrects a mistake using a program which sound = buzzer.
- 11.- Improved auto attenuator in satellite.
- 12.- Added pulse response recording in datalogger.